

## CLAIMS

WHAT IS CLAIMED IS

1. A fuel cell system comprising:

5 a fuel cell which generates electric energy by electro-chemical reaction;

a first tank which holds fluid discharged from the fuel cell;

10 a second tank arranged to receive fluid that is stored the first tank;

a first drive device arranged to move the fluid in the first tank to the second tank; and

a controller arranged to control operation of the first drive device at a time of non-power-generation.

15

2. The fuel cell system according to Claim 1, wherein the time of non-power-generation is a time after power generation is finished, and the second tank includes an aqueous solution tank which holds fuel aqueous solution to be supplied to the fuel cell.

20

3. The fuel cell system according to Claim 2, further comprising a first channel which connects the first tank with the aqueous solution tank.

25

4. The fuel cell system according to Claim 2, further comprising a second drive device arranged to move fluid in the

fuel cell to the first tank,

wherein the controller is arranged to control operation of the second drive device after power generation is finished.

5 5. The fuel cell system according to Claim 4, further comprising:

a first channel disposed so as to connect the first tank with the aqueous solution tank; and

a second channel disposed so as to connect the fuel cell  
10 with the first tank.

6. The fuel cell system according to Claim 5, wherein the controller is arranged to control operation of the first drive device and the second drive device based on temperature  
15 information of the fuel cell system.

7. The fuel cell system according to Claim 5, wherein the controller operates the first drive device and the second drive device again in a predetermined amount of time after operating  
20 the first drive device and the second drive device.

8. The fuel cell system according to Claim 5, wherein the aqueous solution tank has a volume V which satisfies:

25

$$V \geq v_1 + (v_2 + v_3 + v_4 + v_5) \times \left(1 + \frac{p_2}{p_1 - p_2}\right)$$

where  $V$  represents the volume of the aqueous solution tank;  
v1 represents the volume of methanol aqueous solution in the  
aqueous solution tank during power generation; v2 represents the  
5 volume of fluid storable by the first tank; v3 represents the  
volume of fluid which can remain in the first channel; v4  
represents the volume of fluid which can remain in the second  
channel; v5 represents the volume of fluid which can remain in  
the fuel cell; p1 represents a concentration of fuel; and p2  
10 represents a maximum concentration of fuel aqueous solution.

9. The fuel cell system according to Claim 1, further  
comprising an air pump arranged to supply the fuel cell with air  
necessary for generation of electric energy, and a sensor  
15 arranged to detect an amount of fluid in the first tank; wherein  
the first tank includes an exhaust port;  
the first drive device includes a water pump;  
the controller is arranged to control operation of the water  
pump based on the amount of fluid in the first tank detected by  
20 the sensor, at the time of non-power-generation.

10. The fuel cell system according to Claim 9, wherein the time  
of non-power-generation is before power generation is started,  
and the controller is arranged to control operation of the water  
25 pump before operating the air pump.

11. The fuel cell system according to Claim 9, wherein the time of non-power-generation is after power generation is finished.

12. The fuel cell system according to Claim 9, wherein the  
5 controller is arranged to control the operation of the water pump based on the volume of fluid in the first tank detected by the sensor, at a predetermined time interval after power generation is finished.

10 13. The fuel cell system according to Claim 9, wherein the second tank includes an aqueous solution tank which holds fuel aqueous solution to be supplied to the fuel cell.

14. The fuel cell system according to Claim 13, wherein the fuel  
15 cell is disposed at a lower position than the aqueous solution tank.

15. The fuel cell system according to Claim 9, wherein the system is a direct methanol fuel cell system.

20 16. Transport equipment comprising the fuel cell system according to Claim 1.

17. A control method for a fuel cell system including a fuel  
25 cell which generates electric energy by electro-chemical reaction, a first tank which holds fluid discharged from the fuel cell and

a second tank to which fluid in the first tank is introduced,  
wherein the method comprises the step of:

moving fluid in the first tank to the second tank at a time  
of non-power-generation.

5

18. The control method for a fuel cell system according to Claim  
17, wherein the second tank includes an aqueous solution tank  
which holds fuel aqueous solution to be supplied to the fuel cell,  
and the step of moving fluid in the first tank to the second tank  
10 is performed such that the fluid in the first tank is moved to  
the aqueous solution tank after power generation is finished.

19. The control method for a fuel cell system according to Claim  
18, wherein the fuel cell system further includes a first channel  
15 which connects the first tank with the aqueous solution tank,  
fluid in the first tank being moved to the aqueous solution  
tank via the first channel after power generation is finished.

20. The control method for a fuel cell system according to Claim  
20 18, wherein fluid in the fuel cell is moved to the aqueous  
solution tank via the first tank after power generation is  
finished.

21. The control method for a fuel cell system according to Claim  
25 19, wherein the fuel cell system further includes a second  
channel which connects the fuel cell with the first tank, and

wherein fluid in the fuel cell and fluid in the second channel are moved to the aqueous solution tank via the first tank and the first channel after power generation is finished.

5 22. The control method for a fuel cell system according to Claim 21, wherein the fluid is moved to the aqueous solution tank based on temperature information of the fuel cell system after power generation is finished.

10 23. The control method for a fuel cell system according to Claim 21, wherein after power generation is finished and the fluid is moved to the aqueous solution tank, fluid is moved to the aqueous solution tank in a predetermined amount of time.

15 24. The control method for a fuel cell system according to Claim 17, wherein the fuel cell system further includes an air pump for supplying the fuel cell with air necessary for the generation of electric energy, the first tank having an exhaust port, and fluid in the first tank is moved to the second tank if an amount of  
20 fluid in the first tank exceeds a predetermined amount, at the time of non-power-generation.

25 25. The control method for a fuel cell system according to Claim 24, wherein fluid in the first tank is moved to the second tank prior to driving the air pump if the amount of fluid in the first tank exceeds a predetermined amount, before power generation is

started.

26. The control method for a fuel cell system according to Claim  
24 or 25, wherein fluid in the first tank is moved to the second  
5 tank if the amount of fluid in the first tank exceeds a  
predetermined amount, after power generation is finished.

27. The control method for a fuel cell system according to Claim  
24, wherein the process of moving fluid in the first tank to the  
10 second tank if the amount of fluid in the first tank exceeds a  
predetermined amount is performed at a predetermined time  
interval, after power generation is finished.